

VersaTEK Small

LED Site & Area
Series



Versatility by Design

The VersaTEK Small LED Site & Area Series by LEOTEK blends architectural styling, performance & unsurpassed reliability in a simple, retrofit friendly design delivering up to 28,325 lumens & efficacies as high as 188 LPW.

For end users seeking a value-driven solution without compromising product quality or reliability, the VersaTEK Small Site & Area Series delivers significant energy and maintenance savings, providing up to 70-80% combined savings over its installed life compared to traditional HID luminaires for exceptional payback, lowest TCO and ROI.

With a clean free flowing low profile design, the pole arm mount blends seamlessly into any environment or application. Factory-rotatable performance area optics and multiple field-installable shield options deliver exceptional uniformity that looks amazing, while providing visual safety & trespass control for demanding installations.


Pair this with a wide range of fixture & control options, including our LEOLink ILS™ Intelligent Lighting System, optional motion sensors, DALI D4i drivers, D4i receptacles and part night dimming control capabilities. Advanced controls can help maximize energy savings, simplify maintenance, improve asset visibility, and extend system life.

Key Features, Details & Specs

- 4,577 to 28,325 delivered lumens w/ efficacies up to 188+ LPW
- True 50-400+ watt HID replacement (70%+ energy savings)
- (3) slipfitter, round/square fixed & adjustable pole arm, mast arm mount options
- Performance Selector option for field-adjustable output ranging from 30-100%
- LEOLink ILS™ Intelligent Lighting System & wireless 'NB01P' smart controller option
- Next-gen performance LED platform, Site & Area, Roadway optics & shielding
- 2700K, 3000K, 4000K & 5000K CCT options available (including 80CRI options)
- Weighs only 20-22 lbs. for easy & safe single person installation
- Tool-free access with optional tool-free removable electrical 'Power Door'
- 10kV integral surge standard, 20kV extreme surge option available
- Entire luminaire & optical assembly is rated IP66
- 50°C (122°F) high-ambient rated standard for maximum electrical component life
- A360 die-cast low copper content alloy (< 0.6%) for max paint adhesion & life
- 5,000-hour salt spray finish standard (coastal finish available)
- 3G vibration rated suitable for high winds, overpasses, bridges, etc.
- Tested before & after rigorous 2-hour burn-in cycle
- BAA compliant, BABA option available, assembled in the USA (San Jose, CA)
- LEOTEK factory 10-year warranty is standard

Typical Applications

Any Large Open Areas & Parking Lots
Business Parks & Campuses
Commercial & Retail Plazas
College Campuses
Hotels & Hospitality
Industrial Parks



Integral Tool-Free Access Design

Tool-free electrical access & removable hinged door w/ integral VersaKICK fixed open door kickstand design for ease of installation or maintenance (hassle-free design compatible w/ most lineman safety gloves)




Hassle Free Installation & Maintenance Features

Optional terminal block, a self-centering mast arm 'star' design assists with leveling to a tenon and a retrofit friendly quick mount pole arm (pole arm mount retrofits up to 5.25" bolt spacing for easy single person no drill install)



Tool-Free Removable Power Door Option

All serviceable electrical components mounted to a Power Door that is accessed & removable without tools in less than 15 seconds (undo MOLEX connectors, push two spring clips to unlock door, slide forward to remove)



VersaTEK Small LED Site & Area Series



'MAF' mast arm fitter mount (w/ optional 'PCR7CR' shown)

Ordering Information

Sample Catalog No. VTSSA-36A-MV-40K8-T3R-WH-CF-P9-SPM-D4I-TLR4U-TB-SP2-WL1-PWRD-SF277-BABA

Product*	LED Code	Voltage	Color Temp CRI	Optical Distribution	Finish*	Performance Code*	Mounting Options
VTSSA VersaTEK Small Site & Area	36A 72A 36 or 72 LEDs Gen-A	MV 120-277V HV 347-480V	27K7 2700K, 70CRI 30K7 3000K, 70CRI 40K7 4000K, 70CRI 50K7 5000K, 70CRI 30K8 3000K, 80CRI 40K8 4000K, 80CRI 50K8 5000K, 80CRI	NR Narrow Roadway MR Medium Roadway WR Wide Roadway T2R Type-2R T2F Type-2F T3R Type-3R T3F Type-3F T4R Type-4R T4F Type-4F T5 Type-5 AFR Auto Front Row ORR Optics Rotated Right ORL Optics Rotated Left	BK Black DB1 Dark Bronze (RAL8019) WH White GY Gray CF Coastal Finish *Consult factory for custom finish options, pricing & leadtimes.	P1 P2 P3 P4 P5 P6 P7 P8 P9* P10 P11 *36A is P9 max	SPM Universal Square Pole Arm Mount RPM Universal Round Pole Arm Mount MAF Horizontal Mast Arm Fitter (compatible w/ 1-5/8", 2-3/8" and 3" O.D. tenons) WM Wall Mount Fixed (compatible w/ 3" & 4" square/octagonal recessed J-boxes) WMSC Wall Mount Fixed w/ Surface Conduit J-Box AWM Adjustable Wall Mount (compatible w/ 3" & 4" square/octagonal recessed J-boxes) AWMSC Adjustable Wall Mount w/ Surface Conduit J-Box ASPM Universal Square Pole Adjustable Arm Mount ARPM Universal Round Pole Adjustable Arm Mount

*If Build America, Buy America Act (BABA) compliance is required, please refer to 'BABA Domestic Build Option' located under 'General Options' and refer to footnote #14 for additional details.

Driver* & Control Options (*0-10V drivers are standard)	General Options	General Accessories*
D4I ^{2,5} DALI D4i Driver TLR4U ^{2,3,5} DALI 4-PIN Twist Lock Receptacle (upper of housing receptacle location) TLR4L ^{2,3,5} DALI 4-PIN Twist Lock Receptacle (lower driver door receptacle location) PCR7CR ^{2,8} ANSI 7-wire Control Ready Receptacle SC Shorting Cap (factory installed) LLPC ⁴ Long Life Photocontrol PS ⁵ Field Adjustable Performance Selector PND1 ⁶ Part Night Dimming V1 PND2 ⁶ Part Night Dimming V2 PND3 ⁶ Part Night Dimming V3 MSL3 ^{7,8} Motion Sensor w/ L3 Lens MSL7 ^{7,8} Motion Sensor w/ L7 Lens MSL3P ^{7,9} Motion Sensor w/ L3 Lens w/ PCR7 MSL7P ^{7,9} Motion Sensor w/ L7 Lens w/ PCR7 LEOLink ILS™ Intelligent Lighting System ¹⁰ * See VTSSA specification sheet for LEOLink ordering & system details * (refer to LEOLink ILS specification sheets for complete specification & ordering information)	TFL Tamper free latch (driver electrical door) TB 3-position Terminal Block SP2 ¹¹ 20kV/10kA Extreme Surge, Fail-to-On LSSP2 20kV/10kA Extreme Surge, Fail-to-Off WL Wattage Label, ANSI C136.15-2015 compliant WL1 Wattage Label, ANSI C136.15-2020 compliant DSC Optional Driver Door Safety Cable PWRD Power Door Option (tool-free removable door w/ serviceable electrical items) SFXXX ¹² Single Fuse ('XXX' = specify 120, 277, 347V) DFXXX ¹² Double Fuse ('XXX' = specify 208, 240, 480V) BLS ¹³ Enhanced Back Light Shield (factory installed) VHS 80 Degree Cutoff Shield (factory installed) FSS ¹³ Front Side Shield (factory installed) CSS ¹³ Cul-de-sac Shield (factory installed) BABA ¹⁴ BABA Domestic Build Option Build America, Buy America Act Compliant (meets Oct. 1, 2026 final US assembly, 55% content material requirements)	Shield Accessories TBS-VTS Top, Bottom Shield LRS-VTS Left, Right Side Shield 4SS-VTS 4-sided Shield BDS-VTS Barn Door Shield VS-VTS Poly Vandal Shield WG-VTS Wire Guard BLS-VTSXXX ^{13,15} Enhanced Backlight Shield (snap-on) VHS-VTSXXX ¹⁵ 80-Degree Cutoff Shield (snap-on) FSS-VTSXXX ^{13,15} Front Side Shield (snap-on) CSS-VTSXXX ^{13,15} Cul-de-sac Shield (snap-on) ('XXX' = specify 36A or 72A LED Code) BSK Bird Deterrent Spider Kit Controls Accessories LLPCM/V Long Life Photocontrol MV LLPCH/V Long Life Photocontrol HV FSIR100 MS Configuration Tool *Accessories are ordered & shipped separately, not to be included in the luminaire's catalog number. (requires field installation)

- 80CRI option only available in 3000K, 4000K & 5000K CCTs and may have longer leadtimes (contact factory).
- For full 100% D4i DALI functionality a 'PCR7CR', 'TLR4U' or 'TLR4L' must be selected w/ 'D4I' DALI driver option. DALI compatible node or sensor (by others). 'D4I' DALI driver not compatible w/ 'NB01P05/10' smart controller.
- 'TLR4U' & 'TLR4L' twist lock receptacle options requires 'D4I' driver option to be selected.
- 'LLPC' requires 'PCR7CR' option to be selected (does not ship installed, included w/ luminaire).
- 'PS' Performance Selector enables field adjustable light output dimming control from specified Performance Code, not compatible with DALI driver option.
- 'PND' options only available w/ 'MV' 120-277V (contact factory for 'HV' 347-480V availability).
7. Motion Sensor options only available w/ 'SPM', 'RPM', 'MAF', 'WM' and 'WMSC' horizontal mounting options.
- 'PCR7CR' control ready receptacle for use with wireless 7-PIN control node (by others).
- 'MSL3', 'MSL7' motion sensors require secondary controls for ON/OFF capability (ex. time clock or 0-10V by others).
- 'MSL3P', 'MSL7P' motion sensors includes a PCR7 photocontrol receptacle for use with a twist lock photocontrol for ON/OFF capability (for use with our 'LLPC' or photocontrol by others, PINS 6 & 7 are not wired for controls, not compatible w/ wireless nodes).
- 'NB01P05/10' requires 'PCR7CR' option, only available in 'MV' 120-277V (contact factory for 'HV' 347-480V). 'NB01P05/10' is a cellular based NEMA 7-PIN Smart Controller, RenAI subscription and network data plan required (see spec sheet for details).
- 10kV/5kA surge, fail-to-on is included standard ('SP1'). 12. For single or double fusing, 'XXX' must specify required voltage. 13.'BLS-VTS', 'FSS-VTS' and 'CSS-VTS' shields are not available for use with the 'T5' Type-5 optical distribution.
- 'BABA' option must be specified to meet Oct. 1, 2026 Build America, Buy America Act (BABA) guidelines. Failure to specify the 'BABA' ordering code will result in receiving non-BABA compliant product (w/ no recourse for an RMA, product exchange or refund).
- For snap-on shield accessory items, 'XXX' must specify 36A or 72A LED Code to receive the proper quantity of shields required for field installation.

Nominal Performance Data 4000K & 5000K

(36A, Type-2R, 70CRI, 25°C ambient)

Performance Code	P1	P2	P3	P4	P5	P6	P7	P8	P9
Lumens¹	5,406	6,982	8,507	9,983	11,408	12,783	14,109	15,383	16,609
System Wattage (W)	30	39	49	59	68	77	86	97	106
Efficacy (Lm/W)	180	179	174	169	168	166	164	159	157
HID Replacement	50-100W		175W	200W	250W			350W	

(72A, Type-2R, 70CRI, 25°C ambient)


Performance Code	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11
Lumens¹	13,932	15,476	16,996	18,494	19,968	21,419	22,847	24,251	25,632	26,690	28,325
System Wattage (W)	74	83	92	101	109	117	126	135	144	155	165
Efficacy (Lm/W)	188	186	185	183	183	183	181	180	178	174	172
HID Replacement	250W		350W				400W+				

1. Normal tolerance ± 10% due to factors including distribution type, LED bin variance, driver variance and ambient temperatures.

* Please refer to VersaTEK product specification sheets for additional ordering information & product details *

'SPM' Square Pole Arm Mount Dimensions

Can retrofit up to 5.25" max. bolt spacing w/ no drilling required



© 2026 LEOTEK Electronics U.S.A. Corporation

All specifications are subject to change without notice and all reported values are nominal/typical measured under lab conditions @ 25° C (77° F).
VTSSA Sell Sheet 09-23-26 V1



LEOTEK
1955 Lundy Ave., San Jose, CA, 95131
1.408.380.1788



www.LEOTEK.com



orders@leotek.com