



**IES ROAD REPORT**

**PHOTOMETRIC FILENAME : GCM4-60J-MV-27K-2R-XX-225 S.IES**

**DESCRIPTIVE INFORMATION (From Photometric File)**

IESNA:LM-63-2002  
[TESTLAB] Scaled from NVLAP LM-79 for GCM4-60J-MV-30K-2R-XX-240-PCR7  
[ISSUE DATE] 11/10/2022  
[MANUFAC] Leotek Electronics USA LLC  
[LUMCAT] GCM4-60J-MV-27K-2R-XX-225


**CHARACTERISTICS**

IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	22563
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	143
Total Luminaire Watts	158
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	14507.711
Maximum Candela Angle	70H 72V
Maximum Candela (<90 Degrees Vertical)	14507.711
Maximum Candela Angle (<90 Degrees Vertical)	70H 72V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	2987.711 (13.2% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

**LUMINAIRE CLASSIFICATION SYSTEM (LCS)**

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2101.4	N.A.	9.3
FM - Front-Medium (30-60)	7846.3	N.A.	34.8
FH - Front-High (60-80)	4253.9	N.A.	18.9
FVH - Front-Very High (80-90)	85.1	N.A.	0.4
BL - Back-Low (0-30)	1943.7	N.A.	8.6
BM - Back-Medium (30-60)	4650.0	N.A.	20.6
BH - Back-High (60-80)	1650.6	N.A.	7.3
BVH - Back-Very High (80-90)	31.9	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
<b>Total</b>	<b>22562.9</b>	<b>N.A.</b>	<b>100.0</b>
BUG Rating	B3-U0-G3		


**COEFFICIENTS OF UTILIZATION**



**FLUX DISTRIBUTION**


	Lumens	Percent Of Luminaire
Downward Street Side	14286.7	63.3
Downward House Side	8276.2	36.7
Downward Total	22562.9	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	22562.9	100.0

POLAR GRAPH




Maximum Candela = 14507.711 Located At Horizontal Angle = 70, Vertical Angle = 72  
# 1 - Vertical Plane Through Horizontal Angles (70 - 250) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (72) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height  
 Values Based On 20 Foot Mounting Height  
 1/2 Maximum Candela Trace Shown As Dashed Curve  
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:  
Front: Low=2101.4, Medium=7846.3, High=4253.9, Very High=85.1  
Back: Low=1943.7, Medium= 4650.0, High=1650.6, Very High=31.9  
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3